NK-VN3600

Female One-Touch Couplings on Both Ends Type

NFK
TOP JAPANESE BRAND
SINCE 1971

◆ APPLICATION

- Absorb Movement and Displacement
- Vibration and Noise Reduction
- Compensate for Misalignment
- Pressure and Temperature Resistance
- Extend Equipment Lifespan

◆ FEATURES

- Applicable Media

Water, Oil, Air, Gas, Non-corrosive Chemical...etc
*For others, please contact us for consultation

- Woking Pressure

Up to 2.0Mpa
*Higher Pressure is available on request

- Working Temperature

-20 Deg. C ~ 180 Deg. C.
*Disregard working pressure


- End Connection

BSPT, NPT
*Special standard is available on request



STRUCTURE

No.	Parts	Material
1	Tube	Stainless Steel (304 . 321 . 316L)
2	Braid	Stainless Steel
3	Braid sleeve	Stainless Steel
4	Nipple	Carbon Steel . Stainless Steel
5	Socket	Brass . Carbon Steel . Stainless Steel
6	Female adapter	Brass . Carbon Steel . Stainless Steel



Unit (mm)

SPECIFICATION

Size		Min. Bending Radius	500 OAL		1000 OAL		Min. OAL
DN	Inch		Effective Length	Lateral Movement	Effective Length	Lateral Movement	
DN15	1/2	50	404	123	904	210	500
DN20	3/4	65	396	123	896	210	500
DN25	1	80	384	100	884	200	500
DN32	1 1/4	110	368	90	868	200	500
DN40	1 1/2	120	356	68	856	200	500
DN50	2	135	344	50	844	200	500

DN15 ~ DN25: Calculated on STD Tube, at 1.6 MPa and 40 °C
DN32 ~ DN50: Calculated on SA Tube, at 1.6 MPa and 40 °C

INSTALLATION GUIDE

- Metal flexible hoses should be bent and used only to the radius and lateral movement specified in their guidelines to prevent fatigue and failure.
- Twisting of metal flexible hoses should be avoided while installing and using as well.
- For guidance on dynamic movement, please contact us.

NOTES

- The information in this catalog may be subject to updates or modifications without prior notice.
- Special lengths are available on request.